

# Series **Acron**



# Acron Exact Pearl Mate 30x60 Xs Pb Rc

30x60 XS RC



## Technical Data



Series: ACRON  
 Product: Acron Exact Pearl Mate 30x60 Xs Pb Rc  
 Size: 30x60 XS RC  
 Sales group G.135  
 Type: WALL TILE

Type of material White body  
 Slipperness R:  
 Class:  
 UPEC:  
 Finish: MATT

| Size        | Product type | Pcs/Box | M2/Box | Kg/Box | Boxes/Pallet | M2/Pallet | Kg/Pallet |
|-------------|--------------|---------|--------|--------|--------------|-----------|-----------|
| 30x60 XS RC | Relief       | 9       | 1,620  | 20,666 | 40,000       | 64,800    | 826,640   |

Please note: the contents of this packaging list are for guidance only, the contents of the packaging may vary. Please consult our sales staff for the exact list.

## Technical Data

## Acron Exact Pearl Mate 30x60 Xs Pb Rc

|                  |                       |
|------------------|-----------------------|
| Family:          | <b>WALL TILE MATT</b> |
| Absortion Group: | <b>BIII</b>           |
| Size:            | <b>30x60 XS RC</b>    |
| Worz Size (mm):  | <b>600 x 300 x 7</b>  |



## PHYSICAL CHARACTERISTICS

| CHARACTERISTICS                               | STANDARD            | VALUE                     |
|-----------------------------------------------|---------------------|---------------------------|
| Dimensional tolerances and surface appearance | UNE-EN-ISO 10545-2  | Complies with the standar |
| Water Absortion                               | UNE-EN-ISO 10545-3  | E>10%                     |
| Breaking strenght (N)                         | UNE-EN-ISO 10545-4  | >200                      |
| Flexural tensile strengthn (N/mm2)            | UNE-EN-ISO 10545-4  | >=15                      |
| Thermal shock resistance                      | UNE-EN-ISO 10545-9  | Complies with the standar |
| Cracking resistance                           | UNE-EN-ISO 10545-11 | Complies with the standar |
| Frost resistance                              | UNE-EN-ISO 10545-12 | For indoor use only       |
| Moisture expansion (mm/m)                     | UNE-EN-ISO 10545-10 | 0,2                       |
| Linear thermal expansion from 200°C to 1000°C | UNE-EN-ISO 10545-8  | 5,2x10-6 ?C-1             |
| Reaction to fire                              | UNE-EN-ISO 13501-1  | A1                        |
| DCOF                                          | DCOF                |                           |

**CHEMICAL CHARACTERISTICS**

| CHARACTERISTICS                                      | STANDARD            | VALUE                      |
|------------------------------------------------------|---------------------|----------------------------|
| Resistance to staining                               | UNE-EN-ISO 10545-14 | Complies with the standars |
| Resistrance to chemicals and pool treatment products | UNE-EN-ISO 10545-13 | Complies with the standars |
| Resistance to High concentration acids and bases     | UNE-EN-ISO 10545-13 | MIN HB                     |
| Resistance to Low concentration acids and bases      | UNE-EN-ISO 10545-13 | MIN LB                     |