

Series **Midtown**



Midtown Cream Mate 90x90 SI Rc Antislip

90x90 SL RC



Technical Data



Series: MIDTOWN
 Product: Midtown Cream Mate 90x90 SI Rc Antislip
 Size: 90x90 SL RC
 Sales group G.5092
 Type: Porcelain tiles

Type of material Neutral Body
 Slipperness R: R11B
 Class: Antislip
 UPEC:
 Finish: MATT

| Size | Product type | Pcs/Box | M2/Box | Kg/Box | Boxes/Pallet | M2/Pallet | Kg/Pallet |
|-------------|--------------|---------|--------|--------|--------------|-----------|-----------|
| 90x90 SL RC | Field Tile | 2 | 1,620 | 35,666 | 30,000 | 48,600 | 1069,980 |

Please note: the contents of this packaging list are for guidance only, the contents of the packaging may vary. Please consult our sales staff for the exact list.

Technical Data

Midtown Cream Mate 90x90 SI Rc Antislip

| | |
|------------------|-----------------------------|
| Family: | Porcelain tiles MATT |
| Absortion Group: | Bla |
| Size: | 90x90 SL RC |
| Worz Size (mm): | 900 x 900 x 9 |



PHYSICAL CHARACTERISTICS

| CHARACTERISTICS | STANDARD | VALUE |
|---|---------------------------|---------------------------|
| Dimensional tolerances and surface appearance | UNE-EN-ISO 10545-2 | Complies with the standar |
| Water Absortion | UNE-EN-ISO 10545-3 | E<0,5% |
| Breaking strenght (N) | UNE-EN-ISO 10545-4 | >1300 |
| Flexural tensile strengthn (N/mm2) | UNE-EN-ISO 10545-4 | >=35 |
| Resistance to abrasion (PEI) | UNE-EN-ISO 10545-7 | 4 |
| Thermal shock resistance | UNE-EN-ISO 10545-9 | Complies with the standar |
| Cracking resistance | UNE-EN-ISO 10545-11 | Complies with the standar |
| Frost resistance | UNE-EN-ISO 10545-12 | Complies with the standar |
| Scratch hardness according to Mohs | UNE-EN-ISO 67101 | 6 |
| Slipperness resistance Pendulum | UNE-EN 16165:2022 anexo C | Clase 3 |
| Slipperness resistance Inclined platform | UNE-EN 16165:2022 anexo B | R11 |
| Slipperness resistance Barefoot areas | UNE-EN 16165:2022 anexo A | B |
| Reaction to fire | UNE-EN-ISO 13501-1 | A1 - A1 FL |
| DCOF | DCOF | >0,60 |

CHEMICAL CHARACTERISTICS

| CHARACTERISTICS | STANDARD | VALUE |
|--|---------------------|----------------------------|
| Resistance to staining | UNE-EN-ISO 10545-14 | Complies with the standars |
| Resistrance to chemicals and pool treatment products | UNE-EN-ISO 10545-13 | Complies with the standars |
| Resistance to High concentration acids and bases | UNE-EN-ISO 10545-13 | MIN HB |
| Resistance to Low concentration acids and bases | UNE-EN-ISO 10545-13 | MIN LB |