

# Series **Borneo**



# Borneo Sand Mate 60x120 Xs Rc Pb

60x120 XS RC



## Technical Data



Series: BORNEO  
Product: Borneo Sand Mate 60x120 Xs Rc Pb  
Size: 60x120 XS RC  
Sales group G.182  
Type: WALL TILE

Type of material White body  
Slipperness R:  
Class:  
UPEC:  
Finish: MATT


| Size         | Product type | Pcs/Box | M2/Box | Kg/Box | Boxes/Pallet | M2/Pallet | Kg/Pallet |
|--------------|--------------|---------|--------|--------|--------------|-----------|-----------|
| 60x120 XS RC | Field Tile   | 3       | 2,160  | 27,866 | 30,000       | 64,800    | 835,980   |

Please note: the contents of this packaging list are for guidance only, the contents of the packaging may vary. Please consult our sales staff for the exact list.

## Variations



## Variations



**Technical Data**

**Borneo Sand Mate 60x120 Xs Rc Pb**

Family: **WALL TILE MATT**  
Absortion Group: **BIII**  
Size: **60x120 XS RC**  
Worz Size (mm): **1200 x 600 x 7**



**PHYSICAL CHARACTERISTICS**

| CHARACTERISTICS                               | STANDARD            | VALUE                     |
|-----------------------------------------------|---------------------|---------------------------|
| Dimensional tolerances and surface appearance | UNE-EN-ISO 10545-2  | Complies with the standar |
| Water Absortion                               | UNE-EN-ISO 10545-3  | E>10%                     |
| Breaking strenght (N)                         | UNE-EN-ISO 10545-4  | >200                      |
| Flexural tensile strengthn (N/mm2)            | UNE-EN-ISO 10545-4  | >=15                      |
| Thermal shock resistance                      | UNE-EN-ISO 10545-9  | Complies with the standar |
| Cracking resistance                           | UNE-EN-ISO 10545-11 | Complies with the standar |
| Frost resistance                              | UNE-EN-ISO 10545-12 | For indoor use only       |
| Moisture expansion (mm/m)                     | UNE-EN-ISO 10545-10 | 0,2                       |
| Linear thermal expansion from 200°C to 1000°C | UNE-EN-ISO 10545-8  | 5,2x10-6 ?C-1             |
| Reaction to fire                              | UNE-EN-ISO 13501-1  | A1                        |
| DCOF                                          | DCOF                |                           |

**CHEMICAL CHARACTERISTICS**

| CHARACTERISTICS                                      | STANDARD            | VALUE                      |
|------------------------------------------------------|---------------------|----------------------------|
| Resistance to staining                               | UNE-EN-ISO 10545-14 | Complies with the standars |
| Resistrance to chemicals and pool treatment products | UNE-EN-ISO 10545-13 | Complies with the standars |
| Resistance to High concentration acids and bases     | UNE-EN-ISO 10545-13 | MIN HB                     |
| Resistance to Low concentration acids and bases      | UNE-EN-ISO 10545-13 | MIN LB                     |