


Series **Glaciar**




Glaciar Mate 60x120 Xs Rc Pb

60x120 XS RC



Technical Data



Series: GLACIAR
Product: Glaciar Mate 60x120 Xs Rc Pb
Size: 60x120 XS RC
Sales group G.182
Type: WALL TILE

Type of material White body
Slipperness R:
Class:
UPEC:
Finish: MATT


Size	Product type	Pcs/Box	M2/Box	Kg/Box	Boxes/Pallet	M2/Pallet	Kg/Pallet
60x120 XS RC	Field Tile	3	2,160	27,866	36,000	77,760	1003,176

Please note: the contents of this packaging list are for guidance only, the contents of the packaging may vary. Please consult our sales staff for the exact list.

Technical Data

Glaciar Mate 60x120 Xs Rc Pb

Family:	WALL TILE MATT
Absortion Group:	BIII
Size:	60x120 XS RC
Worz Size (mm):	1200 x 600 x 7



PHYSICAL CHARACTERISTICS

CHARACTERISTICS	STANDARD	VALUE
Dimensional tolerances and surface appearance	UNE-EN-ISO 10545-2	Complies with the standar
Water Absortion	UNE-EN-ISO 10545-3	E>10%
Breaking strenght (N)	UNE-EN-ISO 10545-4	>200
Flexural tensile strengthn (N/mm2)	UNE-EN-ISO 10545-4	>=15
Thermal shock resistance	UNE-EN-ISO 10545-9	Complies with the standar
Cracking resistance	UNE-EN-ISO 10545-11	Complies with the standar
Frost resistance	UNE-EN-ISO 10545-12	For indoor use only
Moisture expansion (mm/m)	UNE-EN-ISO 10545-10	0,2
Linear thermal expansion from 200°C to 1000°C	UNE-EN-ISO 10545-8	5,2x10-6 ?C-1
Reaction to fire	UNE-EN-ISO 13501-1	A1
DCOF	DCOF	

CHEMICAL CHARACTERISTICS

CHARACTERISTICS	STANDARD	VALUE
Resistance to staining	UNE-EN-ISO 10545-14	Complies with the standars
Resistrance to chemicals and pool treatment products	UNE-EN-ISO 10545-13	Complies with the standars
Resistance to High concentration acids and bases	UNE-EN-ISO 10545-13	MIN HB
Resistance to Low concentration acids and bases	UNE-EN-ISO 10545-13	MIN LB