

Series **Granite**



Granite Grey Mate 30x90 Rc

30x90 RC



Technical Data



Series: GRANITE

Product: Granite Grey Mate 30x90 Rc

Size: 30x90 RC

Sales group G.104

Type: WALL TILE

Type of material White body

Slipperiness R:

Class:

UPEC:

Finish: MATT

| Size | Product type | Pcs/Box | M2/Box | Kg/Box | Boxes/Pallet | M2/Pallet | Kg/Pallet |
|----------|--------------|---------|--------|--------|--------------|-----------|-----------|
| 30x90 RC | Field Tile | 5 | 1,350 | 20,413 | 63,000 | 85,050 | 1286,019 |

Please note: the contents of this packaging list are for guidance only, the contents of the packaging may vary. Please consult our sales staff for the exact list.

The results shown represent an indicative approximation. This document does not constitute a contractual relationship. To place orders or check product availability, please contact the company.

Technical Data

Granite Grey Mate 30x90 Rc



| | |
|------------------|------------------------|
| Family: | WALL TILE MATT |
| Absortion Group: | BIII |
| Size: | 30x90 RC |
| Worz Size (mm): | 900 x 300 x 8,7 |

PHYSICAL CHARACTERISTICS

| CHARACTERISTICS | STANDARD | VALUE |
|---|---------------------|---------------------------|
| Dimensional tolerances and surface appearance | UNE-EN-ISO 10545-2 | Complies with the standar |
| Water Absortion | UNE-EN-ISO 10545-3 | E>10% |
| Breaking strenght (N) | UNE-EN-ISO 10545-4 | >600 |
| Flexural tensile strengthn (N/mm ²) | UNE-EN-ISO 10545-4 | >12 |
| Thermal shock resistance | UNE-EN-ISO 10545-9 | Complies with the standar |
| Cracking resistance | UNE-EN-ISO 10545-11 | Complies with the standar |
| Frost resistance | UNE-EN-ISO 10545-12 | For indoor use only |
| Moisture expansion (mm/m) | UNE-EN-ISO 10545-10 | 0,2 |
| Linear thermal expansion from 200°C to 1000°C | UNE-EN-ISO 10545-8 | 5,2x10-6 °C-1 |
| Reaction to fire | UNE-EN-ISO 13501-1 | A1 |
| DCOF | DCOF | |

CHEMICAL CHARACTERISTICS

| CHARACTERISTICS | STANDARD | VALUE |
|---|---------------------|----------------------------|
| Resistance to staining | UNE-EN-ISO 10545-14 | Complies with the standars |
| Resistance to chemicals and pool treatment products | UNE-EN-ISO 10545-13 | Complies with the standars |
| Resistance to High concentration acids and bases | UNE-EN-ISO 10545-13 | MIN HB |
| Resistance to Low concentration acids and bases | UNE-EN-ISO 10545-13 | MIN LB |