


# Series **Timeless**



# Timeless Pearl Mate 15x17 N-plus

15x17



## Technical Data



Series: TIMELESS  
Product: Timeless Pearl Mate 15x17 N-plus  
Size: 15x17  
Sales group: G.11  
Type: Porcelain tiles

Type of material: Neutral Body  
Slipperness R: R10B  
Class: Class 2  
UPEC:  
Finish: MATT


Size	Product type	Pcs/Box	M2/Box	Kg/Box	Boxes/Pallet	M2/Pallet	Kg/Pallet
15x17	Field Tile	30	0,570	10,840	80,000	45,600	867,200

Please note: the contents of this packaging list are for guidance only, the contents of the packaging may vary. Please consult our sales staff for the exact list.

Technical Data

Timeless Pearl Mate 15x17 N-plus

Family: **Porcelain tiles MATT**  
Absortion Group: **Bla**  
Size: **15x17**  
Worz Size (mm): **173 x 150.5 x 8,2**



PHYSICAL CHARACTERISTICS

CHARACTERISTICS	STANDARD	VALUE
Dimensional tolerances and surface appearance	UNE-EN-ISO 10545-2	Complies with the standar
Water Absortion	UNE-EN-ISO 10545-3	E<0,5%
Breaking strenght (N)	UNE-EN-ISO 10545-4	>1300
Flexural tensile strengthn (N/mm2)	UNE-EN-ISO 10545-4	>=35
Resistance to abrasion (PEI)	UNE-EN-ISO 10545-7	3
Thermal shock resistance	UNE-EN-ISO 10545-9	Complies with the standar
Cracking resistance	UNE-EN-ISO 10545-11	Complies with the standar
Frost resistance	UNE-EN-ISO 10545-12	Complies with the standar
Scratch hardness according to Mohs	UNE-EN-ISO 67101	5
Slipperness resistance   Pendulum	UNE-EN 16165:2022 anexo C	Clase 2
Slipperness resistance   Inclined platform	UNE-EN 16165:2022 anexo B	R10
Slipperness resistance   Barefoot areas	UNE-EN 16165:2022 anexo A	B
Reaction to fire	UNE-EN-ISO 13501-1	A1 - A1 FL
DCOF	DCOF	>0,42

CHEMICAL CHARACTERISTICS

CHARACTERISTICS	STANDARD	VALUE
Resistance to staining	UNE-EN-ISO 10545-14	Complies with the standars
Resistrance to chemicals and pool treatment products	UNE-EN-ISO 10545-13	Complies with the standars
Resistance to High concentration acids and bases	UNE-EN-ISO 10545-13	MIN HB
Resistance to Low concentration acids and bases	UNE-EN-ISO 10545-13	MIN LB